
TH Earphone Jacks (∅2.5mm)

General Specifications for LJE Series


Insulation Resistance:	100MΩ min. at 500 V DC
Withstanding Voltage:	500 V AC for 1 minute
Contact Resistance:	30mΩ max. (initial)
Soldering Heat Test:	260 ±5°C for 5±1 seconds
Insertion Force:	0.3 to 2.0 Kg
Extraction Force:	0.3 to 2.0 Kg
Mating Cycles:	5,000 times

Mating Plugs for LJE Series (TH Earphone Jacks)


∅ 2.5mm Mono




∅ 3.5mm Mono



∅ 2.5mm Stereo



∅ 3.5mm Stereo





LJE0252-B


RoHS

LJE0252-* (Stereo)










Part No. (Details)



PCB-Layout (Bottom View)


SPECIFICATIONS ARE SUBJECT TO ALTERATION WITHOUT PRIOR NOTICE - DIMENSIONS IN MILLIMETER


TH Earphone Jacks (∅3.5mm)

LJE0357-B


RoHS








Part No. (Details)







PCB-Layout (Bottom View)

LJE0357-3RT (Stereo)


RoHS








Part No. (Details)








PCB-Layout (Bottom View)

LJE0366-*


RoHS








Part No. (Details)






PCB-Layout (Bottom View)


TH Earphone Jacks (∅3.5mm)


LJE0359AM-* (w/o Thread)
LJE0359M-* (with Thread)

RoHS









PCB-Layout (Bottom View)


Part No. (Details)


LJE0359*M-2T	LJE0359*M-3RT	LJE0359*M-3TS	LJE0359*M-4T	LJE0359*M-4R	LJE0359*M-5
2 T 1 S	3 R 2 T 1 S	10TS 2 T 1 S	3 R 11RS 2 T 1 S	3 R 10TS 2 T 1 S	3 R 11RS 10TS 2 T 1 S


LJE0361-*

RoHS









PCB-Layout (Bottom View)


Part No. (Details)


LJE0361-3RT	LJE0361-3TS	LJE0361-4T	LJE0361-4R	LJE0361-5
3 R 2 T 1 S	10TS 2 T 1 S	3 R 11RS 2 T 1 S	3 R 10TS 2 T 1 S	3 R 11RS 10TS 2 T 1 S


LJE0363A-3RT (Stereo, with Metal Ring)
LJE0363-3RT (Stereo, w/o Metal Ring)

RoHS









PCB-Layout (Bottom View)

Part No. (Details)


LJE0363*-3RT
1 S 3 R 2 T


TH Earphone Jacks (∅3.5mm)

LJE0364-*


RoHS








Part No. (Details)







PCB-Layout (Bottom View)


LJE3530K (Stereo)

RoHS










PCB-Layout (Bottom View)


Part No. (Details)





LJE3531 (Stereo)

RoHS










PCB-Layout (Bottom View)

Part No. (Details)



SPECIFICATIONS ARE SUBJECT TO ALTERATION WITHOUT PRIOR NOTICE - DIMENSIONS IN MILLIMETER