
REV.	DATE	ECR NO.	DESCRIPTION
NC	02/03/09	–	INITIAL RELEASE



LENGTH TABLE	
PART NUMBER	LENGTH (IN.)
135104–03–06.00	6.00
135104–03–12.00	12.00
135104–03–24.00	24.00
135104–03–36.00	36.00

NOTE:
1. PERFORM CONTINUITY AND HI–POT TESTING.
2. PACKAGED INDIVIDUALLY IN HEAT SEALED POLY BAG.

4			
3	009–954–341	HEAT SHRINK TUBING, BLACK, 3/16" DIAMETER	A/R FT
2	009–881–206	COAXIAL CABLE, RG316/U DOUBLE BRAID CABLE	A/R FT
1	132182	CONNECTOR, SMA R/A PLUG, GOLD	2
	PN	DESCRIPTION	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	02/03/09
CHECKED	
ISSUED	
SHEET 1 OF 1	

CAD FILE C:/135/135104–03–XX.XX.DWG

Amphenol Connex

PART DESCRIPTION
SMA R/A PLUG TO SMA R/A PLUG
RG316 DB

PART NO. 135104–03–XX.XX

DWG. NO.	REV.	SIZE	SCALE
135104–03–XX.XX.DWG	NC	A	NA